



ATTENTION – SPECIAL OFFERS NOW AVAILABLE !!!

OUR PRICES ARE HITTING THE SUMMER LOW !!!

SO PRICES ARE CURRENTLY REDUCED BY 35% !!!

Offer

Hydr. Cylindrical Grinding Machine RIBON RUR 800 w/ internal grinding attachment



manufacturer: RIBON

type: RUR 800

mach.-nr.: N6/0537

year of construction: 1988* / 2017 tüp.

comm.-nr.: 3990500/009

stock-nr.: 1875

Special Price: 7.650,- € | now 4.972,50 €

The machine can be used for:

- external grinding
- internal grinding
- planar grinding
- cone grinding
- chamfering
- slope grinding

Technical Data

(According to manufacturer)

height of tip: 140 mm

swing – Ø: 280 mm

width of tip: 800 mm

grinding wheel:

diameter: 355x 127 x 32 mm

max. width of full grinding wheel during punch-grinding: 60 mm

max. size total width of grinding wheel set: 70 mm

max. sum of single widths: 32 mm

grinding wheel speeds infinitely adjustable via planetary gear

grinding head:

adjustment of grinding head left – right: 90° each

max. grinding head hub: 180 mm

max hub using hand wheel: 180 mm

autom. interval feed: 0,005 – 0,015 mm

feed via one revolution of the hand wheel: 1,3 mm

feed via one hand wheel unit: 0,005 mm

max. diameter adjustment: 0,05 – 3,0 mm

diameter adjustment via tipping switch: 0,005 mm

diameter adjustment via micro-stop: 0,001 mm

headstock spindle:

8 workpiece speeds, adjustable: 35 – 310 rpm

spindle cone or inner cone of headstock spindle: MK 4

headstock spindle bore: 24 mm

tilting of headstock: -30/+90°

tailstock:

inner cone of quill: MK 2

quill way: 20 mm

table:

max. table tilt: 5° each

max. cone angle: 10°

table speed, adjustable: 190 – 940 mm/Min.

min. table travel using hydraulic movement approx.: 1 mm

1 turn of hand wheel approx.: 15 mm table movement

drive power: approx. 4 kW




weight: approx. 1.600 kg

standing area: W 2,30 x D 1,00 x H 1,50 m

color: blue / grey-white

Features

- positionable internal grinding device
 - manual or automatic operation
 - grinding wheel speed infinitely adjustable
 - upper table for cone grinding with fine adjustment and dial gauge
 - automatic adjustment works as punch grinding adjustment, without adjustment,
 - table-dependent adjustment: # right # left and right # left only
 - creep traverse, spark-out times infinitely adjustable
 - ejecting infinitely adjustable, can be disabled
 - 3 – B. – grinding padding Ø 160 mm, with inner and outer clamps (unused)
 - tailstock centres
 - reducer cap to MK2
 - adjustable table limiter with measuring clock (new)
 - grinding stone puller, adjustable, with diamond
 - wet-grinding equipment
 - central lubrication
 - leveling screws with vibration-dampening feet
 - operating manual
-
- If the year of construction has a “tüp.”-date, that means the machine has been electrically and technically inspected by us on that date.
 - If the year of construction has a “tüb.”-date, that means the machine has been partially overhauled on that date according to the prior owner.
 - If the year of construction is marked “*”, it is the information the prior owner relayed to us or our own estimation.





ProHa-Maschinen
 Owner: Wilfried Jürgens
 Ident-Nr. DE 182722273
 AG Essen HRA 7402

Office
 Egge 3
 45549 Sprockhövel

Warehouse
 58285 Gevelsberg

Collection and delivery by
 appointment only.

Phone 0 23 39 / 121212
 Fax 0 23 39 / 121213

www.proha-maschinen.de
info@proha-maschinen.de